

PROJECT NAME:	_CATALOG NUMBER:
NOTES:	FIXTURE SCHEDULE:

FIXTURE SCHEDULE:\_

Page: 1 of 2

# **LED Shop Light**

**SL Series** 





Linkable up to 4 units



The MaxLite Shop Light is designed to replace traditional fluorescent fixtures in both residential and commercial applications. Developed with a built in on/off chain, linkable 4 units and uniform light distribution, it is ideally suited for workshops, garages, and utility rooms.















#### **FEATURES:**

- Instant full brightness
- Integrated LED lights
- Cool white color temperature (5000K)
- Offered in 42W nominal
- L70 lumen maintenance of 50,000 hours
- 120V only
- Built in on/off pull chain
- Can be chain mounted via chain and hooks provided
- 5ft power cord and plug included
- Linkable up to 4 units
- •Operating temperature -20°F to 104°F

# **APPLICATIONS:**

- Garages
- Basement
- Utility Rooms
- Work Shops
- Attics

### **WARRANTY:**

5-year standard warranty\* (see terms at www.maxlite.com/warranties)

\*Excludes EM/MS versions; component warranty applies. \*Product may be eligible for warranty extension to 10 years for an additional fee. Limitations apply, contact MaxLite for details.

MODEL SELECTION			
ORDER CODE	MODEL NUMBER	DESCRIPTION	DIMENSIONS - (L" X W' X H")
14099808	SL-48421-50	SHOP LIGHT 48" 42W 120V 5000K	48" x 5.2" x 1.9"

## **SPECIFICATIONS:**

ITEM	SPECIFICATION	DETAILS	
ELECTRICAL	Power Consumption (W)	40.1 W	
	Lumens Delivered (lm)	4,890 lm	
	Efficacy (Im/W)	122 lm/W	
	CRI	≥80	
	Color Temperature (K)	5000K	
	L70 Lifetime (hours)	50,000Hrs	
PHYSICAL	Power Factor	≥0.9	
	Input Voltage	120V	
	Mounting	Suspended Mounting	
	Dimension (L x H x W)	48" x 5.2" x 1.9"	
	Operating Temperature	-20°F to 104°F	
	Humidity	20-85% RH, non-condensing	
CERTIFICATION	Certification	FCC, cETLus, Energy Star	
	Material Usage	RoHS compliant; no mercury	
	Environment	Indoor	
	Warranty	5-year standard warranty*	

MAX18084

Phone: 1-800-555-5629 | Fax: 973-244-7333 | Web: www.maxlite.com | E-mail: info@maxlite.com | Revised: 11/11/20 | MaxLite