

LUX LED Flood Light

Applications

Available in 5000K cold white color temperature, the LED modules in this flood light emit a 65° x 120° beam angle from individually-lensed, premium-quality, Nichia SMD LEDs. The fixture's heavy-duty cast-aluminum housing and tempered glass lens are sealed to an IP66 rating to withstand virtually any weather conditions. Ultra-high quality 3030 SMD LED components and an advanced design that provides efficient heat transfer makes these lights maintenance free and allows us to provide a 5-year warranty.

Features

- 65° x 120° beam angle
- Weatherproof (IP66 Rating)
- Cold White Light (5000K)
- DLC & ETL Listed
- 5-year warranty



Specifications

	100W	150W	200W	240W
Light Output	13,500 lumens	20,250 lumens	27,000 lumens	32,400 lumens
Luminous Efficacy	135 lm/W	135 lm/W	135 lm/W	135 lm/W
Power Consumption	100W	150W	200W	240W
Replaces	250W	400W	750W	1000W
Average Lamp Life	50,000 hours	50,000 hours	50,000 hours	50,000 hours
Color	Cool White: 5000K	Cool White: 5000K	Cool White: 5000K	Cool White: 5000K
CRI	70	70	70	70
Base Type	Fixture	Fixture	Fixture	Fixture
Housing Color	Black	Black	Black	Black
Enclosure Rating	IP66 (Protected against dust and high-pressure jets of water)			
Housing Material	Alluminum Alloy and Glass Cover			
Certification	DLC, ETL	DLC, ETL	DLC, ETL	DLC, ETL
Warranty	5 Years	5 Years	5 Years	5 Years